xerox

Product Safety Data Sheet
SDS # : 22-00739
2022-07-11
Revision 1

FD70 Scanner

Product Description	Scanner
Speed (PPM)	140
Mono / Color	Color

ELECTRICAL INPUT INFORMATION

Voltage (Volts)	**100V-240V**
Rated Current (Amperes)	1.5
Frequency (Hertz)	50/60
Phase Connection	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)
Active [1]	48	163.8
Ready[1]	0.66	2.25
Standby[1] (Off/FEMP) [2]	0.12	0.4

[1] Power states defined per ENERGY STAR Program requirements for Imaging Equipment

[2] FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%			
Ambient Temperature	50-95 °F	/	10-35 °C	

PRODUCT SIZE

Depth	12.6 in.	32.1 cm
Width	21.4 in.	54.5 cm
Height	9.1 in.	23.1 cm
Weight	19 lbs	8.6 kg

SPACE REQUIREMENTS   Desktop

For additional information regarding different configurations please contact your local sales representative.

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com